




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04H 1/00, H04N 7/173	A1	(11) International Publication Number: WO 99/18684
		(43) International Publication Date: 15 April 1999 (15.04.99)
<p>(21) International Application Number: PCT/US98/19881</p> <p>(22) International Filing Date: 25 September 1998 (25.09.98)</p> <p>(30) Priority Data: 08/943,987 3 October 1997 (03.10.97) US</p> <p>(71)(72) Applicant and Inventor: ANGLIN, Richard, Jr. [US/US]; 2115 Heather Lane, Del Mar, CA 92014 (US).</p> <p>(74) Agent: GIACCHERINI, Thomas, N.; Anglin & Giaccherini, P.O. Box 1146, Carmel Valley, CA 93924 (US).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>

(54) Title: INTERACTIVE DIGITAL DATA BROADCASTING SYSTEM



(57) Abstract

All existing two-way mobile communications technologies are narrow-band, fixed bandwidth and symmetrical, that is, out-bound and in-bound channel are of size equal. The invention is asymmetrical, the out-bound transmission to the mobile user is much higher in bandwidth than the in-bound channel. Further the out-bound bandwidth is variable; it can be tailored to meet service requirements. The invention comprises a plurality of digital data broadcasting transmitter systems (12) which operate in the frequency bands 2,310-2,320 and 2,345-2,360 MHz (S-band). The invention also includes user terminals (14) which are capable of receiving a plurality of S-band channels, and capable of transmitting in one or more traditional wireless communications bands.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

Interactive Digital Data Broadcasting System

TECHNICAL FIELD

The present invention relates to the field of mobile data broadcasting and communications. More particularly, this invention provides novel methods and apparatus for broadcasting digital data including digital audio programming to mobile, portable and fixed receivers and for receiving digital transmissions from those user terminals. Utilization of the present invention will create new markets for interactive audio and data services as well as image and compressed video both on a subscription and advertiser-supported basis.

BACKGROUND ART

In the United States, several organizations are developing technologies to allow digital signals to be simultaneously broadcast within the same frequency band and on the same channel as existing amplitude modulation ("AM") and frequency modulation ("FM") radio stations, that is, in-band, on-channel ("IBOC"), and technologies to simultaneously transmit digital signals in the same band but in a non-interfering channel adjacent to a FM channel, that is, in-band, adjacent channel ("IBAC"). This technology, if implemented, would allow existing broadcasters to provide a single channel of compact disk ("CD") quality digital programming within the area they currently serve and without additional frequency allocations. In recent comparative testing these systems did not fare well and must be redesigned. Considerable more development and testing is necessary for these systems even to be considered for deployment. Even then, as with exiting AM and FM, these technologies are single fixed channels without interactive capability.

On April 1, 1997, the Federal Communications Commission ("FCC") auctioned two licenses to provide satellite-based digital audio radio services ("DARS") in the United States. Satellite CD Radio, Inc. ("SCDR") and American Mobile Radio Corporation ("AMRC"), a subsidiary of American Mobile Satellite Corporation ("AMSC"), were the winning bidders for the two available licenses in this service respectively (2,320-2,332.5 MHz and 2,332.5-2,345 MHz). Because these are satellite-based systems only, at least three years is required for either of them to commence service. Depending upon the final design of each system, they may offer multiple channels on a nationwide basis only. These DARS systems will not offer regional or local services. Furthermore, they do not provide interactive capability.

Radio Satellite Corporation ("RadioSat") has developed a patented broadcast, navigation and communication system which could be implemented using only narrowband L-band mobile satellite services ("MSS") available from AMSC in the United States and TMI, Inc. in Canada. The RadioSat mobile terminal is conceptually designed to deliver a few channels of digital audio and interactive data

services, including global positioning system ("GPS") information. RadioSat has been actively pursuing opportunities to implement its services but has had no success in over six years of trying.

A number of both terrestrial and satellite mobile data systems exist, all of which systems are fixed narrow bandwidth and limited capacity. None of these systems offer or are likely to offer audio, image or compressed video services because of both bandwidth and regulatory limitations. Further, these systems are focused on commercial applications only such as fleet management and routing, not entertainment or information services. Examples of such mobile data systems include: Cellular Digital Packet Data ("CDPD"), RAM Mobile Data ("RAM"), Advanced Radio Data Information Service ("ARDIS"), AMSC, TMI, Qualcomm, Inc. OmniTRACS® and the "Big LEO" and "Little LEO" satellite systems.

No system exists today which provides asymmetrical digital data communications services to mobile users. The development of a system that provides high bandwidth data broadcast transmission to mobile users and narrowband transmission from mobile users would contribute an important advancement in the communications industry. Such asymmetrical transmission capability would respond to and support a variety of interactive applications, such as Internet and World Wide Web access and multi-channel interactive audio programming.

DISCLOSURE OF THE INVENTION

The present invention encompasses methods and apparatus to enable high bandwidth digital data broadcast transmission to mobile users in conjunction with traditional wireless communications systems such as cellular, Personal Communication Services ("PCS") and Enhanced Specialized Mobile Radio ("ESMR") for communications in-bound from users. The disclosed invention can provide a variety of interactive audio and data services as well as image and compressed video to mobile users. The disclosed invention responds to increasing mobility and demands for real-time information.

A preferred embodiment of the invention comprises three (3) elements: broadcast transmission capacity in the newly allocated and recently auctioned Wireless Communications Service ("WCS") bands, 2,310-2,320 and 2,345-2,360 MHz; user equipment capable of receiving transmissions in these bands that have embedded in them traditional wireless phones, and a network management system ("NMS").

The present invention offers a number of synergies and advantages. First, all existing two-way mobile communications technologies are narrow band, fixed bandwidth and symmetrical, that is, out-bound and in-bound channels are of equal size. The disclosed invention is asymmetrical, the out-bound transmission to the mobile user is much higher in bandwidth than the in-bound channel. Further, the out-bound bandwidth is variable; it can be tailored to meet service requirements.

Second, in a preferred embodiment by obtaining outbound transmission capacity from WCS licensees, no further license is required from the FCC. Only Part 15 type acceptance of terminal equipment is required. It is envisaged that similar advantages will be obtained under the regulations of other countries around the world.

Third, the disclosed invention enables a variety of audio, data, image and compressed video services primarily to mobile users heretofore unavailable.

Fourth, in a preferred embodiment of the invention, the use of Internet Protocol enables services such as voice, video, image, audio, and data which have previously been provided by narrowband networks. Alternative embodiments of the invention may utilize the following frequency bands: 902 to 5 928 MHz; 2,400 to 2,483.5 MHz; or 5,725 to 5,825 MHz.

Instead of being transmitted at fixed, compressed data rates, audio channels will continuously be transmitted at optimal data rates to guarantee the desired quality perceived by listeners. A preferred embodiment of the disclosed invention comprises a number of "FM quality" channels of audio programming at 64 kbps as well as several "CD quality" channels at 128 kbps. For example, a classical 10 channel will broadcast a symphony at 128 kbps and news segments at 64 kbps while maintaining the same perceived quality. Different channels will be dynamically multiplexed to benefit from these variable data rates so that at each moment the "best" use is made of the available capacity and throughput.

To enable subscription-based services and multiple listeners per subscription, a preferred 15 embodiment of the disclosed invention utilizes subscriber identity module ("SIM") technology. SIM cards the size of a credit card will contain subscriber characteristics and programming choices and will enable subscribers to listen to their preferred programming regardless of the receiver used.

Progressive Networks, Inc. has deployed RealAudio™, a method of transmitting audio programming via the Internet using Transmission Control Protocol/Internet Protocol ("TCP/IP"). An 20 alternative embodiment of the disclosed invention comprises application of this and similar transmission protocol technologies to the mobile environment.

Among other data services a preferred embodiment of the disclosed invention enables transmission of an Electronic Program Guide ("EPG") to all receivers. This guide provides information on current and forthcoming programming or special events available via the disclosed invention.

Because the present invention integrates data communications with audio broadcasting, the 25 listener can be drawn into an interactive environment. A preferred embodiment of the disclosed invention enables transmission of program selection, composer and other information as an integral part of the audio broadcast. Additionally, in an alternative embodiment of the disclosed invention, if the program is taken from a CD, the listener is able to purchase that CD and have it delivered to his home or office simply by 30 pushing a "button" on the receiver touch-screen. A further alternative embodiment of the disclosed invention, enables the listener to access a database or other works by the same composer and order them as well.

Alternative embodiments of the invention enable a number of interactive information services unrelated to audio programming. For example, the invention maybe used to provide continuous stock and 35 bond quotations selected by the subscriber. Through strategic relationships with stock brokers, a further alternative embodiment of the disclosed invention can even enable trades.

The FCC has mandated that wireless communications systems implement technologies to provide location information to be used by enhanced 911 ("E911") systems in responding to emergency situations. Various technologies are under development that utilize the transmissions from a wireless phone to determine its location. Location information thus determined may also be used to provide a number of value-added data and information services via the disclosed invention. For example, the disclosed invention may be used to provide directory information about restaurants, hotels, attractions and other traveler services specific to the area of the caller upon request.

A further alternative embodiment of the disclosed invention comprises receivers including a screen for the display of images or video. The screen may be used to display maps, weather forecasts or other graphic information. A further alternative embodiment of the disclosed invention comprises a thermal printer for hard copies of transmitted or displayed information.

An appreciation of the other aims and objectives of the present invention and a more complete and comprehensive understanding of this invention may be obtained by studying the following description of a preferred embodiment and by referring to the accompanying drawings.

A BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows the elements of the *Interactive Digital Data Broadcasting System*.

Figure 2 shows a functional block diagram of the user terminal.

Figure 3 shows a functional block diagram of the user interface.

Figure 4 shows the overall interactive digital data broadcasting network.

BEST MODE FOR CARRYING OUT THE INVENTION

A preferred embodiment of the *Interactive Digital Data Broadcasting System* 10 is shown in Figure 1. This embodiment comprises a plurality of digital data broadcasting transmitter systems 12 operating in the frequency bands 2,310-2,320 and 2,345-2,360 MHz (S-band) in the United States; a user terminal 14 capable of receiving a plurality of channels in the said frequency bands and capable of transmitting in one or more traditional wireless communications bands; a plurality of receiving systems 16 for transmission from a user terminal 14; and a network management center ("NMC") 18.

Figure 2 shows a user terminal 14 which comprises an antenna system 20 capable of receiving multiple channels of broadband data broadcast transmissions in said frequency bands 2,310-2,320 and 2,345-2,360 MHz 22 and transmitting on any traditional wireless communications technology 24; a receiver 26; digital signal processing 28; a user interface 30; a transmitter operating in a traditional wireless communications system band 32; and a software operating system 34 to control the functions of the user terminal 14.

Digital signal processing 28 encompasses de-multiplexing of the received broadcast signal, processing the channels of programming and data, and delivering them to the appropriate port of the user interface 30.

5 A preferred embodiment of the user interface 30 as shown in Figure 3 comprises an audio system 36 for listening to programming, a display 38, a plurality of output ports for the utilization of broadcast data 40, and a plurality input ports 42 for user interactivity.

Preferred embodiments of the display 38 comprise a touch screen liquid crystal display ("LCD"), field-emission display ("FED") or other flat-panel display technology.

10 A more comprehensive understanding of the functioning of a preferred embodiment of the invention may be obtained by examining Figure 4. Digital audio programming is created by programming originators 44 and transmitted to the network management center 18 via traditional public and private networks 46. There the programming is assembled and prepared for transmission.

15 The various channels of digital data are then sent via traditional public and private networks 46 to the plurality of S-band transmitter systems 12 for broadcast to users. A typical broadcast 48 is comprised of a plurality of channels of digital audio along with concomitant data information such as composition, title, composer name, length remaining and the program publisher. While the audio is playing via the audio system 36, concomitant data relating to the audio is displayed on the user interface 30 display 38.

20 If the user wishes to purchase the CD from which the audio selection is taken, he or she touches the appropriate area of the touch-screen display 38. A message is transmitted 50 via a traditional wireless communication system 16 to the network management center 18. In a preferred embodiment, these messages are transmitted using a range which generally extends from 1 KHz to 3 GHz. The network management center 18 then sends the order message via traditional public and private networks 46 to a value-added service provider 52 which fulfills the request and delivers the CD to the user.

25 In an alternative embodiment of the invention, a satellite 54 may be employed to distribute signals to the transmitter 12. Alternative embodiments of the invention may utilize the following frequency bands: 902 to 928 MHz; 2,400 to 2,483.5 MHz; or 5,725 to 5,825 MHz.

INDUSTRIAL APPLICABILITY

The present invention will offer enhanced high-bandwidth digital communications to mobile users around the globe.

CONCLUSION

Although the present invention has been described in detail with reference to one or more preferred embodiments, persons possessing ordinary skill in the art to which this invention pertains will appreciate that various modifications and enhancements may be made without departing from the spirit and scope of the Claims that follow. The various alternatives for an interactive digital data broadcasting system that have been disclosed above are intended to educate the reader about preferred embodiments of the invention, and are not intended to constrain the limits of the invention or the scope of Claims. The List of Reference Characters which follow is intended to provide the reader with a convenient means of identifying elements of the invention in the Specification and Drawings. This list is not intended to delineate or narrow the scope of the Claims.

LIST OF REFERENCE CHARACTERS

10	<i>Interactive Digital Data Broadcasting System</i>
12	Digital data broadcasting transmitter
14	User terminal
16	Traditional wireless receiving system
18	Network management center
20	User terminal antenna system
22	Antenna for receiving broadcast signals
24	Antenna for transmitting via traditional wireless communications systems
26	Broadcast receiver
28	Digital signal processing
30	User interface
32	Wireless communications system transmitter
34	User terminal software operating system
36	Audio system
38	User terminal display
40	Data output port
42	Data input port
44	Programming originator
46	Traditional public and private networks
48	Broadcast signal
50	Message signal
52	Value-added service provider
54	Satellite

CLAIMS

What is claimed is:

1. A communications system comprising a digital data broadcasting transmitter (12) operating with a relatively high bandwidth, a user terminal (14) for receiving signals (48) from said transmitter and for transmitting signals (50), and network management means (18) for controlling the flow of signals in the system, characterized in that the signals transmitted by the user terminal (14) have a relatively low bandwidth, in that the user terminal (14) incorporates data input means (38, 42) to enable a user to respond to incoming data from the transmitter (12) and to control the signals (50) transmitted by the user terminal, in that a receiver (16) is provided for receiving the signals (50) transmitted by the user terminal, and in that the receiver (16) is connected directly or indirectly to means (52) for responding to the signals (50) transmitted by the user terminal.
2. A communications system according to claim 1, wherein the signals (48) from said transmitter (12) lie in the frequency bands 2.310 to 2.320 GHz and 2.345 to 2.360 GHz.
3. A communications system according to claim 1 or 2, wherein the signals (50) transmitted by said user terminal (14) lie in frequency bands from 1 KHz to 3 GHz.
4. A communications system according to any preceding claim, wherein the user terminal (14) comprises a user interface device (30) comprising an audio system (36), a display device (38) and data input means (42) for operation by the user.
5. A communications system according to claim 4, wherein the data input means is incorporated in the display device (38) in the form of a touch screen.
6. A communications system according to any preceding claim, wherein the signals (48) from said transmitter include digital audio signals together with concomitant data information.

5 7. A communications system according to claim 6, wherein the concomitant data information identifies an audio item being broadcast and actuation of the data input means (38, 42) causes the transmission of signals (50) which incorporate messages which are routed by the network management means (18) to said responding means (52), said responding means (52) being associated with a service provider which is arranged to subsequently supply a copy of said audio item and/or copies of one or more associated audio, data and/or video items.

8. A communications system according to any preceding claim, wherein the network management means (18) communicates with the transmitter (12) and/or the receiver (16) and/or the responding means (52) by signal lines.

9. A communications system according to any preceding claim, wherein the network management means (18) communicates with at least the transmitter (12) via a satellite (54).

10. A communications system comprising:

a digital data broadcasting transmitter (12); said transmitter (12) operating in the (S-band) frequencies;

5 a user terminal (14) for receiving signals from said transmitter (12); said user terminal (14) also for transmitting signals (50) in frequency bands from 1 KHz to 3 GHz.(16);


a receiving system (16) for transmission from a user terminal (14) to a mobile subscriber;

an interactive means (38, 42) for accepting a request for service from a subscriber; and

a network management center (18) for controlling the flow of signals through the network.

11. A communications system as claimed in any preceding claim, in which said transmission from a user terminal (14) is in the frequency bands 2,310-2,320 and 2,345-2,360 MHz.

12. A communications system as claimed in any preceding claim, in which said transmission from a user terminal (14) is in the frequency bands 902 to 928 MHz.
 13. A communications system as claimed in any preceding claim, in which said transmission from a user terminal (14) is in the frequency bands 2,400 to 2,483.5 MHz.
 14. A communications system as claimed in any preceding claim, in which said transmission from a user terminal (14) is in the frequency bands 5,725 to 5,825 MHz.
 15. A communications system as claimed in any preceding claim, in which a satellite (54) is used to distribute signals to said transmitters (12).
 16. A communications system according to any preceding claim, wherein the signals (48) from said transmitter (12) use an Internet Protocol (IP).
 17. A communications system according to any preceding claim, wherein the signals (48) from said transmitter (12) lie in the frequency bands 2.400 GHz to 2.483.5 GHz.
 18. A communications system according to any preceding claim, wherein the signals (48) from said transmitter (12) lie in the frequency bands 5.725 GHz to 5.825 GHz.
-



10

FIG. 1




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

Int lional Application No

PCT/US 98/19881

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04H1/00 H04N7/173

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04H H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 28904 A (BELL ATLANTIC NETWORK SERVICES) 19 September 1996 see abstract see page 10, line 7 - page 13, line 11 see claims 1,20 see figures 6-8	1-18
X	US 5 586 121 A (GRONSKI JAN M ET AL) 17 December 1996 see abstract see column 1, line 35 - column 2, line 10 see claims 1-4,6,56	1-3,8,9
A	see figures 1,2,4 --- -/--	4

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

5 February 1999

Date of mailing of the international search report

15/02/1999

Name and mailing address of the ISA

European Patent Office, P. B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Simon, V

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 98/19881

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No.
X	WO 93 05593 A (HYBRID NETWORKS INC) 18 March 1993 see abstract see page 2, line 20 - page 3, line 13 see figures 1,2,5 ---	1-5
P,X	GB 2 313 981 A (ROKE MANOR RESEARCH) 10 December 1997 see abstract see page 12, line 4 - page 13, line 21 see claims 1,10,14 see figure 1 ---	1-5, 10-18
P,X	US 5 706 048 A (DAVIS MARK BRUCE) 6 January 1998 see abstract see column 5, line 45 - column 6, line 56 see figures 6,7 ---	1-5,8,9
P,X	PATENT ABSTRACTS OF JAPAN vol. 098, no. 003, 27 February 1998 & JP 09 307564 A (CASIO COMPUT CO LTD), 28 November 1997 see abstract ---	1-5
P,X	US 5 805 825 A (DANNEELS GUNNER D ET AL) 8 September 1998 see abstract see claim 11 see figures 1-4 ---	1-3
A	WO 96 38002 A (BELLSOUTH CORP) 28 November 1996 see abstract see claim 1 see figures 1,2,7 ---	1-7
A	WO 96 37069 A (IMAGETEL INTERNATIONAL INC) 21 November 1996 see abstract see claims 16,29 -----	1,5


INTERNATIONAL SEARCH REPORT

Information on patent family members

Int: ional Application No

PCT/US 98/19881

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9628904 A	19-09-1996	US 5651010 A	22-07-1997
		US 5729549 A	17-03-1998
		US 5822324 A	13-10-1998
		AU 5365496 A	02-10-1996
		AU 5424496 A	02-10-1996
		AU 5424696 A	02-10-1996
		AU 5424796 A	02-10-1996
		AU 5424896 A	02-10-1996
		AU 5424996 A	02-10-1996
		AU 5425096 A	02-10-1996
		AU 5425296 A	02-10-1996
		WO 9628903 A	19-09-1996
		WO 9628905 A	19-09-1996
		WO 9628906 A	19-09-1996
		WO 9628902 A	19-09-1996
		WO 9628908 A	19-09-1996
		WO 9628909 A	19-09-1996
		WO 9628910 A	19-09-1996
		US 5646942 A	08-07-1997
		US 5559808 A	24-09-1996
		US 5610916 A	11-03-1998
		US 5666365 A	09-09-1997
		US 5852612 A	22-12-1998
		US 5751707 A	12-05-1998
US 5586121 A	17-12-1996	EP 0830756 A	25-03-1998
		WO 9633562 A	24-10-1996
		US 5818845 A	06-10-1998
		US 5828655 A	27-10-1998
		US 5859852 A	12-01-1999
WO 9305593 A	18-03-1993	AU 2554392 A	05-04-1993
		EP 0603269 A	29-06-1994
		US 5347304 A	13-09-1994
		US RE35774 E	21-04-1998
GB 2313981 A	10-12-1997	NONE	
US 5706048 A	06-01-1998	NONE	
US 5805825 A	08-09-1998	NONE	
WO 9638002 A	28-11-1996	AU 5928596 A	11-12-1996
		CA 2221099 A	28-11-1996
		EP 0829167 A	18-03-1998
		NO 975357 A	21-01-1998
WO 9637069 A	21-11-1996	US 5793415 A	11-08-1998
		AU 5793896 A	29-11-1996

**10****FIG. 1**




FIG. 2




FIG. 3




FIG. 4